

a locking mechanism located on the bottom end of the flexible body;

a first notch located on the flexible body at a distance from ~~a point at which the top end meets the cylindrical tube;~~

a second notch located on the flexible body at a distance from the bottom end; and

a cylindrical body ~~defining a cross with~~ having a length defined between a first end and a second end wherein the first end is a pointed end and further wherein the second end is a flat end wherein the cylindrical body is formed by a first part and a second part wherein the first part has a length defined between the first end and the second end wherein the first part has a uniform width between the first end and the second end and further wherein the second part forms a cross at a distance from the second end wherein the first part is removably attached to the second part;

~~a first part having a uniform width and a length defined between the pointed end and the flat end; and~~

~~a second part defining a cross with a length defined between a pointed end and a flat end wherein the first part and the second part define the cylindrical body and further wherein the top end of the flexible hollow body is removably attached to the second part of the cylindrical body.~~

Claim 2 (previously amended): The catheter assembly of Claim 1 further comprising:

a locking mechanism located at the flat end of the cylindrical body wherein the first part and the removable second part are locked together.

Claim 3 (previously amended): The catheter assembly of Claim 1 further comprising:

a cylindrical portion wherein the pointed end of the cylindrical body gradually tapers to the cylindrical portion.

Claim 4 (previously amended): The catheter assembly of Claim 1 wherein the cylindrical body has sufficient structural strength to penetrate through skin and into a subcutaneous layer of a body.

Claim 5 (previously amended): The catheter assembly of Claim 1 further comprising:

a recessed portion along the length of the first part; and
a protruding element defined in shape by a right angle located along the recessed portion of the first part.

Claim 6 (previously amended): The catheter assembly of Claim 1 further comprising:

a protrusion along the length of the removable second part of the cylindrical body wherein the recessed portion along the length of the first part may readily accept the protrusion along

the length of the removable second part.

Claim 7 (previously amended): A catheter assembly for placing within a body, the catheter assembly comprising:

- a flexible hollow body defining a length between a top end and a bottom end wherein the top end is closed and wherein the top end tapers to a cylindrical tube;

- a diameter defined by the cylindrical tube;

- a width defined by the bottom end of the flexible body wherein the width is greater than the diameter;

- a locking mechanism located on the bottom end of the flexible body;

- a first notch located a distance from a point at which the top end meets the cylindrical tube;

- a second notch located a distance from the bottom end;

- a cylinder having a length defined between a pointed end and a second end wherein the top end of the flexible hollow body is removably attached to the pointed end of the cylinder;

- a first hole located a distance from the pointed end of the cylinder;

- a leg attached to the bottom end of the cylinder;

- a second hole located on the leg of the cylinder; and

- a thread connected to the cylinder from the second hole to the first hole.

Claim 8 (previously amended): The catheter assembly of Claim 7 further comprising:

a groove cut into the cylinder having a length defined between the first hole and the pointed end.

Claim 9 (previously amended): The catheter assembly of Claim 7 further comprising:

a locking mechanism located on the leg of the cylindrical body.

Claim 10 (previously amended): The catheter assembly of Claim 7 further comprising:

a cylindrical portion wherein the pointed end of the cylinder gradually tapers to the cylindrical portion.

Claim 11 (previously amended): The catheter assembly of Claim 7 wherein the cylinder has sufficient structural strength to penetrate through skin and into a subcutaneous layer of a body.

Claim 12 (currently amended): A catheter for infusing a local anesthetic, the catheter comprising:

a flexible hollow body ~~defining~~ having a length defined between a pointed end and a bottom end wherein the pointed end is closed wherein the flexible hollow body is ~~the pointed end~~ tapers to a cylindrical tube having a diameter wherein the bottom end of the flexible hollow body has a width greater than the diameter and further wherein the flexible hollow body has a

plurality of holes defining passageways from inside of the flexible hollow body to points exterior to the flexible hollow body;

~~a diameter defined by the cylindrical tube;~~

~~a width defined by the bottom end of the flexible body wherein the width is greater than the diameter;~~

a locking mechanism located on the bottom end of the flexible body; and

a first notch located on the flexible hollow body at a distance between from a point at which the pointed end and the plurality of holes meets the cylindrical tube and further wherein the notch is impermeable; and

~~a second notch located a distance from the bottom end.~~

Claim 13 (original): The catheter of Claim 12 wherein the flexible hollow body is constructed of a porous material.

Claim 14 (canceled)

Claim 15 (previously amended): A method for introducing a catheter into a body of a patient wherein the body includes skin and a subcutaneous layer, the method comprising the steps of:

providing a flexible hollow body defining a length between a top end and a bottom end and having a notch located a distance from the top end;

providing a second notch located a distance from the bottom

end;

providing a first part having a length defined between a pointed end and a flat end;

providing a second part having a length defined between the pointed end and the flat end wherein the first part and the second part define a cylindrical body and further wherein the second part is removable;

providing a locking mechanism located at the flat end of the cylindrical body wherein the first part and the second part are locked together;

piercing the skin and the subcutaneous layer of the body with the pointed end of the cylindrical body;

pushing the cylindrical body through the subcutaneous layer wherein the cylindrical body is exposed outside an exit site of the body;

removing the second part of the cylindrical body;

attaching the notch of the flexible hollow body to the first part of the cylindrical body;

pulling the first part of the cylindrical body and the flexible hollow body into the subcutaneous layer and the entry site; and

removing the first part of the cylindrical body from the flexible hollow body and pulling the flexible hollow body into

the subcutaneous layer.

Claim 16 (previously amended): The method of Claim 15 further comprising the step of:

preventing the flexible hollow body from slipping.

Claim 17 (previously amended): The method of Claim 15 further comprising the step of:

suturing the flexible hollow body to the skin of the body.

Claim 18 (previously amended): The method of Claim 15 further comprising the step of:

attaching the flexible hollow body to the first part of the cylindrical body by placing the top end of the flexible hollow body on the first part of the cylindrical body.

Claim 19 (previously amended): The method of Claim 15 further comprising the step of:

securing the flexible hollow body to the first part of the cylindrical body with a thread.

Claim 20 (previously amended): The method of Claim 15 further comprising the step of:

securing the flexible hollow body to the first part of the cylindrical body by fitting the flexible hollow body to a notch on the first part of the cylindrical body.

Claim 21 (previously amended): The catheter assembly of Claim 1 wherein the flexible hollow body is constructed of a porous

material.

Claim 22 (previously amended): The catheter assembly of Claim 1 wherein the flexible hollow body has a plurality of holes.

Claim 23 (previously amended): The catheter assembly of Claim 7 wherein the flexible hollow body is constructed of a porous material.

Claim 24 (previously amended): The catheter assembly of Claim 7 wherein the flexible hollow body has a plurality of holes.

Claim 25 (previously amended): The method of Claim 15 wherein the flexible hollow body is constructed of a porous material.

Claim 26 (previously amended): The method of Claim 15 wherein the flexible hollow body has a plurality of holes.